AUSQUEST LIMITED
ABN 35 091 542 451

30 October 2019

Australian Securities Exchange
Level 40, Central Park
152 – 158 St George's Terrace
Perth WA 6000

By electronic lodgement

Dear Sir/ Madam

TANGADEE – JORC TABLE

The Company note the lodgement on 30 October 2019 of its Quarterly Activities and Cashflow Report for the period ended 30 September 2019. Included below is a JORC Table for the soil sampling program at the Tangadee Zinc Project that was inadvertently omitted from the release.

Yours sincerely

Henko Vos
Company Secretary

JORC Code, 2012 Edition – Table 1 Report Soil Sampling – Tangadee Zinc Project

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	• *Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.* • *Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.* • *Aspects of the determination of mineralisation that are Material to the Public Report.* • *In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.*	• Soil sampling was completed along lines spaced 500m and 1000m apart at 100m sample intervals within AusQuest E52/3603. • Sample locations were recorded by hand-held GPS. • Soil sampling sites were logged by the sampler and recorded on a sampling spread sheet • Each soil sample was collected by digging a 10 to 20 cm deep hole and screening the material to pass a 400 microns (µm) sieve. • Approximately 200g of material was collected in a numbered kraft packet.
Drilling techniques	• *Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).*	• No drilling undertaken
Drill sample recovery	• *Method of recording and assessing core and chip sample recoveries and results assessed.* • *Measures taken to maximise sample recovery and ensure representative nature of the samples.* • *Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.*	• No drilling undertaken
Logging	• *Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.* • *Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.* • *The total length and percentage of the relevant intersections logged.*	• No drilling undertaken

Criteria	JORC Code explanation	Commentary
Sub-sampling techniques and sample preparation	• *If core, whether cut or sawn and whether quarter, half or all core taken.* • *If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.* • *For all sample types, the nature, quality and appropriateness of the sample preparation technique.* • *Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.* • *Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.* • *Whether sample sizes are appropriate to the grain size of the material being sampled.*	• No sub-sampling was completed
Quality of assay data and laboratory tests	• *The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.* • *For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.* • *Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.*	• The samples were submitted to Intertek Genalysis Maddington, WA, for 48 element suite 4A/MS48 • Samples were subjected to a multi-acid digest, including Hydrofluoric, Nitric, Perchloric and Hydrochloric acids, in Teflon tubes providing close to a total digest for most elements. • Samples were analysed (48 elements) by Inductively Coupled Plasma Mass Spectrometry.
Verification of sampling and assaying	• *The verification of significant intersections by either independent or alternative company personnel.* • *The use of twinned holes.* • *Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.* • *Discuss any adjustment to assay data.*	• Field sample locations were compiled onto Excel spreadsheets for merging with assay data. • Digital data is regularly backed-up on the company's servers.
Location of data points	• *Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.* • *Specification of the grid system used.* • *Quality and adequacy of topographic control.*	• Sample locations are established with a handheld GPS to +/- 5m accuracy.
Data spacing and distribution	• *Data spacing for reporting of Exploration Results.* • *Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.* • *Whether sample compositing has been applied.*	• Samples were collected on lines 500m and 1000m apart at 100m intervals.
Orientation of data in relation to	• *Whether the orientation of sampling achieves unbiased sampling of possible*	• Sample grid lines were generally oriented

Criteria	JORC Code explanation	Commentary
geological structure	*structures and the extent to which this is known, considering the deposit type.* • *If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.*	perpendicular to the strike of the target horizon.
Sample security	• *The measures taken to ensure sample security.*	• Samples were securely sealed in the field, followed by packing into larger sealed plastic bags or boxes for transport to the Perth office.
Audits or reviews	• *The results of any audits or reviews of sampling techniques and data.*	• No audits or reviews have been carried out on the sampling to date.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	• *Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.* • *The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.*	• The Tangadee Project is centered at ~7305000N and 670000E (GDA94 Zone 50), approximately 150 km south west of Newman in Western Australia. • Tenement holdings include granted Exploration Licence E52/3603. • The Tangadee Project is subject to a Strategic Alliance Agreement with South32 who can earn 70% by spending US$4.0M. • Aboriginal heritage surveys are routinely completed ahead of ground disturbing activities
Exploration done by other parties	• *Acknowledgment and appraisal of exploration by other parties.*	• Previous exploration by Rio Tinto between 1998 and 2001 was the most meaningful. It included stream and rock-chip sampling, IP Surveys over two target areas and 10 RC drill holes testing a variety of anomalies within the Kiangi Creek Formation. Anomalous Zn was found but deemed too low to be of interest. Periodic work by other companies is not considered to be effective over the areas the Company is exploring.
Geology	• *Deposit type, geological setting and style of mineralisation.*	• The Tangadee project is targeting sediment hosted

Criteria	JORC Code explanation	Commentary
		zinc mineralisation similar to NW Queensland. Black shale horizons within the Kiangi Creek Formation within the Edmund Basin in WA are the target horizons

Drill hole Information	• *A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:*
	  ○ *easting and northing of the drill hole collar*
	  ○ *elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar*
	  ○ *dip and azimuth of the hole*
	  ○ *down hole length and interception depth*
	  ○ *hole length.*
	• *If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.*
		• No drilling undertaken

Data aggregation methods	• *In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.* • *Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.* • *The assumptions used for any reporting of metal equivalent values should be clearly stated.*	• No drilling undertaken
Relationship between mineralisation widths and intercept lengths	• *These relationships are particularly important in the reporting of Exploration Results.* • *If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.* • *If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').*	• No drilling undertaken
Diagrams	• *Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.*	• Soil sediment sample locations and selected element anomalies are provided in the ASX release.
Balanced reporting	• *Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.*	• Representative reporting of assay results is included in the ASX release.

Criteria	JORC Code explanation	Commentary
Other substantive exploration data	• *Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.*	• The area was selected for sampling based on geological and geophysical data interpretations by the company.
Further work	• *The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).* • *Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.*	• Proposals of further work will be done after a thorough analysis of the data is completed.